

## tesa® 4280 PVO

### PP Shipping Tape for Carton Sealing

tesa® 4280 is a self-adhesive tape based on a 25µm PP-film and a synthetic rubber adhesive. The tape is ideal for sealing and packaging of light- and medium-weight cartons. The packing tape features easy unwinding, is suitable for manual application, and is compatible with any handheld dispenser. The carton sealing tape features a short dwell time before reaching final adhesion power, and is very tacky, allowing for fast and precise positioning during application. tesa® 4280 performs best when applied in moderate temperatures and indoor settings. The packing tape shows excellent adhesive properties on both polar and non-polar surfaces.

### Main Application

\*tesa® 4280 is a multipurpose carton sealing and packaging tape, ideal for light- and medium-weight cartons.

\*The packing tape can be used either manually or with automatic sealing equipment.

\*The tape features easy unwinding and good adhesion to a wide range of surfaces.

### Technical Data

▪ Backing material	PP film	▪ Adhesion to steel	4.8 N/cm
▪ Total thickness	42 µm	▪ Elongation at break	145 %
▪ Type of adhesive	synthetic rubber	▪ Tensile strength	40 N/cm

### Properties

▪ Manual application	yes
----------------------	-----

### Additional Information

Available colours: brown and transparent.

For latest information on this product please visit <http://l.tesa.com/?ip=04280>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.